

# SFAR-S-6RO

SFAR-S-6RO has 6x RO (Relay Outputs). Relay Outputs are selectable normally closed or normally open (NC/NO) type relay outputs 250 V AC/24 V DC max. **3 A/10 A**. Each channel can be individually configured in one of several modes. Built-in **RS485** interface allows to easy connection over **Modbus RTU/ASCII** protocol with a PLC makes the modules an external I/O. The use of **32-bit ARM** core processor provides fast processing and communication with the baud rate from 2400 to 115200 bps. The module is equipped with a set of **LEDs** used to indicate the status of outputs, power supply and RS485 communication. This feature is useful for diagnostic purposes and helping to find errors.

Built-in mini **USB** allows for initial configuration of the unit without power supply.

To simplify installation the modules have been equipped with **Quick Connector** system. Using dedicated **SFAR-S-LINK** cable allows to connect up to 15 modules which provide both RS485 communication and power supply.

## Key Features

- 6x galvanic isolated Relay Output
- Separate contacts for NC and NO options
- 10 A 24 V DC or 5 A 250 V AC on each output
- Watchdog function
- Built-in LEDs for device status indication
- Modbus RTU/ASCII communication
- Baud rate: 2400 bps to 115200 bps
- Up to 128 modules on the bus
- Dedicated TCP/IP to Modbus RTU/ASCII gateway device SFAR-S-ETH
- Built-in mini USB type B port for configuration
- Fast and easy connection with SFAR-S-LINK
- Space-saving housing, DIN rail mount



# SFAR-S-6R0

## Specification

### Relay Outputs (RO)

- Relay Output (NC/NO) max. 10 A @ 24 V DC, 5 A @ 250 V AC

### Platform

- ARM Cortex-M3

### Communication

- Interface RS485 half-duplex
- Up to 128 devices on the bus
- Protocol: Modbus RTU/ASCII
- Baud rate: 2400 to 115200 bps
- Interface mini USB type B

### Power supply

- 12-24 V DC  $\pm 20\%$

### Housing

- Dimension WxHxD: 22.7x110.9x119.1 mm (0.894x4.366x4.689 in)
- Construction: UL approved, self-extinguishing plastic (PC/ABS)
- DIN rail mounting DIN (DIN EN 50022 norm)
- Cooling: internal air circulation

### Environment

- Operating temperature: -10°C to 50°C (14°F to 122°F)
- Storage temperature: -40°C to 85°C (-40°F to 185°F)
- Relative humidity: 5% to 95%, no condensation
- Ingress Protection Rating: IP40 – for indoor installation

### Dimensions

